



As lane and 'walking stick-shaped' device

On the Type DE too, the bolted cutting units with 3mm shell also ensure the greatest stability.

The Type DE vine trimmer also features individually adjustable side cutting units with separate collision protection devices, frame with hydraulic lateral tilt, single-acting height adjustments and common cutting unit width adjustment.



For further informations visit www.freilauber.de or just scan the QR-Code.

From your authorised dealer



Vine trimmer Type DE

Standard equipment and extras



Collision protection at the rear, front and side. **Aluminium clamping** bar for easy re-tensioning of the V-belt and additional stabilisation of the cutting unit.



Practical support trolley for easy attachment and detachment. No jacks or forklifts required.



Large blades and low rotational speed, as well as the 90 mm V-belt pulley with cover, guarantee a significantly longer service life. No botrytis centrifuge and no turbo wear.



Easy to attach. No hoses on the bonnet



A horizontal blade with fixed axle and separate oil motor ensures the greatest stability and longest service life. No guide rollers are necessary.



Wide adjustment range, for lanes from 160 cm to approx. 250 cm.

Technical Data

- Cutting length: Horizontal 1 blade (70 cm) with separate oil motor;
 vertical 3 blades (148/160 cm) or 4 blades (176 cm)
- Three control units are required. Upon request joystick controller with double-acting cylinder for height adjustment, as well as separate width and tilt adjustment on the cutting units; in this case only one control unit required
- Operating pressure is approx. 50 bar at 10 L / min
- High-grade steel