



# Vine trimmer Type WR

**With linear width adjustment for better weight distribution**

Even in working position, the frame, with its large linear width adjustment range, always remains in central alignment with the tractor. This ensures significantly better weight distribution and reduced risk of tipping. At the same time, frame tilt is fully maintained at both sides.

The tilt cylinders are fitted with lock valves as standard. The cutting unit, which is mounted at the centre of gravity, features wear-free plain bearing guides. The bolted cutting units with 3mm shell ensure the greatest cutting unit stability.

The Type WR vine trimmer features individually adjustable side cutting units (upon request also electric) with separate collision protection on three sides. The frame can be used universally, for example for de-leafers or post drivers.



For further informations visit  
[www.freilauber.de](http://www.freilauber.de) or just scan  
the QR-Code.

From your authorised dealer

# Vine trimmer Type WR

## Standard equipment and extras



**Collision protection** at the rear, front and side. **Aluminium clamping** bar for easy re-tensioning of the V-belt and additional stabilisation of the cutting unit.



During transport and when used in sharp-angled rows, the cutting unit is driven in front of the tractor, which is advantageous when turning on difficult terrain. No hoses or valves in the field of vision.



**Large blades and low rotational speed**, as well as the 90 mm V-belt pulley with cover, guarantee a significantly longer service life. No botrytis centrifuge and no turbo wear.



**Practical support trolley** for easy attachment and detachment. No jacks or forklifts required.



**A horizontal blade** with fixed axle and separate oil motor ensures the greatest stability and longest service life. No guide rollers are necessary.



**Easy to attach.** No hoses on the bonnet.



**Optional controller** with two joysticks. Only one control unit necessary.

## Technical Data

- Cutting length: Horizontal 1 blade (70 cm) with drive via fan belt with separate oil motor; vertical 3 blades (148/160 cm) or 4 blades (176 cm), other lengths upon request.
- Two double-acting and one single-acting control unit required.
- The working width is adjustable from 40–65 cm.
- Operating pressure is approx. 50 bar at 10 L / min
- High-grade steel