



Robust subsoiler for optimum aeration of the soil

The free-cleaning subsoiler type Hektor is characterised by its robust design and can be used very flexibly.

It is available with 2 to 7 tines in various widths and the 30 mm thick tines with side wings are designed for a working depth of up to 50 cm. The penetration angle is calculated so that the tines dig progressively into the soil. This reduces the load on the frame and tractor. The points and side wings are coated with Hardox, ensuring a service life that is up to 3 - 4 times longer.

The double spiked roller ensures perfect shredding of the ripped soil.

## Dimen sions

Width	Number of tines	Weight
1,30m	3	700kg
1,50m	3	730kg
2,00m	5	860kg
2,50m	6	970kg
3,00m	7	1.100kg



## Subsoiler type Hektor for liquid fertiliser Efficient and loss-free application of liquid fertiliser into the soil

The freilauber subsoiler type Hektor for liquid fertiliser is equipped with a tank that is available in different volume sizes.

The liquid fertiliser is fed into the soil by an electric pump via a pipe attached to the tine.

The specially developed height-adjustable pressure roller seals the soil immediately after penetration into the ground. The pressure roller is attached individually to each tine.

The application rate is regulated via a nozzle.

There is an ISO bus control for the entire unit, which ensures that the fertiliser can be applied in a targeted manner with the Hektor.





You can find more information at www.freilauber.de or simply scan the QR code.

At your authorised dealer